

# Up-Lift

## UT Series

### Multi Mast Man Lifts

Up-Lift UT multi mast personnel lifts are compact and light weight in construction. Their high strength extruded aluminium masts provide stable platforms for personnel undertaking prolonged aerial work. Apart from the five standard platform heights included in the UT series, other platform heights can be made to order.

Up-Lift UT elevated work platforms enable installation, cleaning, decorating, painting, signing and maintenance, in indoor and/or outdoor settings. They find application in hotels, restaurants, department stores, emporiums, shopping centres, airport departure lounges, sports stadiums, convention centres, as well as factories, hospitals, universities and colleges. The smaller models are designed to pass through standard doorways and into elevator lifts and are especially suited for use in confined spaces.

#### Key features of the UT model:

- 1/ Back-up power for emergency descend
- 2/ Smaller models with under 2 metres stored height
- 3/ Extending or non-extending platform cages
- 4/ Outrigger indicator lights
- 5/ Descend alarm
- 6/ Two person capacity with larger platform area (excluding UT52 & UT58)
- 7/ 1 year parts & labour and 5 years structural warranty
- 8/ AC or DC model available – DC model includes battery & charger



MODEL	UT20	UT23	UT26	UT33	UT36	UT40	UT46	UT52	UT58
Max Platform Height (m)	6.1	7.2	8.0	10.1	11.0	12.3	14.2	16.0	18.0
Max Working Height (m)	8.1	9.2	10.0	12.1	13.0	14.2	16.2	18.0	20.0
Rated Load (kg)	200	200	200	200	200	200	150	150	150
Stored Dimensions (m)	1.8x0.86 x1.1	1.8x0.86 x1.1	1.8x0.86 x2.0	1.8x0.86 x2.0	1.8x0.86 x2.0	1.8x0.86 x2.08	2.0x0.9 x2.8	2.0x0.9 x2.8	2.4x1.24 x1.1
Platform Dimension (m)	1.7x0.7 x1.1	1.7x0.7 x1.1	1.7x0.7 x1.1	1.7x0.7 x1.1	1.7x0.7 x1.1	1.7x0.7 x1.1	1.9x0.7 x1.1	1.9x0.7 x1.1	1.9x0.7 x1.1
Outriggers Foot-Print (m)	2.1x2.8	2.1x2.8	2.1x3.1	2.1x3.1	2.1x3.1	2.1x3.1	2.35x2.75	2.35x2.75	2.9x3.8
Voltage AC/DC Model (v)	230/12	230/12	230/12	230/12	230/12	230/12	230/12	230/12	230/12
Total Weight AC/DC Model (kg)	500/545	540/584	580/622	620/662	680/722	750/792	1386/1470	1420/1504	2380
Power Rating AC/DC Model (kW)	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	1.1/1.6	2.2